

## 1. Product and Company Identification

**Product name:** Rix Premium Hydraulic ISO 46  
**Grades:** ISO VG 46  
**Use:** Lubricating oil for hydraulic equipment  
**Company:** Rix Petroleum Limited  
 Witham House  
 45 Spyvee Street  
 Hull  
 HU8 7JR  
 Telephone No: (Hull) 01482 224422

## 2. Composition/Information on Ingredients

No	Name	EC-No.	CAS-No.	%-mass	Symbol(s)	R Phrases
1	Severely solvent refined mineral oil (IP346 DMSO extract < 3 %)			Ca. 95	-	-
3	Butylated phenol	204-884-0	128-39-2	0.1 - 0.3	N	R51/53

No substances are present in concentrations regarded to present a hazard (Directive 1999/45/EC).

The Symbols and R-phrases in section 2 apply only to individual constituents. See section 16 for the text of these R-phrases.

## 3. Hazards Identification

**Symbol(s):**

**Product Classification:** None

## 4. FIRST AID MEASURES

**Eyes:** Flush the eye with copious amounts of water. No emergency measures are necessary but if adverse eye effects follow, refer for medical attention.

**Skin:** Wash the contaminated skin thoroughly with soap and water. No emergency measures are necessary but if adverse skin effects follow, refer for medical attention.

**Inhalation:** Remove the affected person to fresh air. If recovery is not rapid, obtain medical attention.

**Ingestion:** DO NOT INDUCE VOMITING. No emergency measures are needed but if adverse health effects follow, refer for medical attention.

**Additional Information:**

## 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	<b>Recommended:</b> Dry chemical, foam, CO <sub>2</sub> , water mist. <b>Not to be used:</b> Direct water jet. Use water ONLY to keep fire-exposed containers cool.
<b>Specific exposure hazards:</b>	Slight flammability hazard when exposed to heat or flame.
<b>Special protective equipment for firefighters:</b>	Use self-contained breathing equipment when fighting fire in confined spaces.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions:</b>	No special measures needed.
<b>Environmental precautions:</b>	Water may be used to flush spills away from sources of ignition. Do not allow the product to enter public drainage system or open water courses.
<b>Methods for cleaning up:</b>	Absorb and scrape up.
<b>Absorbent materials:</b>	Sand or active clay.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Avoid prolonged or repeated skin contact. Avoid inhalation of vapour, mist or fume. Do not wear contaminated clothing.
<b>Storage:</b>	Keep containers tightly closed.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Engineering measures:</b>	No special measures needed.
<b>Control parameters:</b>	TWA TLV (ACGIH) : 5 mg/m <sup>3</sup> for oil mist. However, in all circumstances exposure should be kept as low as reasonably possible by good ventilation and safe working practices.
<b>Respiratory protection:</b>	Inhalation of the vapours, fumes or mists should be avoided by safe working practices and good ventilation.
<b>Eye protection:</b>	If there is a risk of splashing while handling product, eye protection should be worn (e.g. full face shield or goggles with side shields).
<b>Hand/skin protection:</b>	Prolonged and repeated skin contact should be avoided by the use of clean gloves and clean overalls. PVC or nitrile gloves may be suitable.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Oily liquid
<b>Colour:</b>	Light yellow
<b>Appearance:</b>	Bright & clear
<b>Odour:</b>	Characteristic
<b>pH:</b>	Neutral
<b>Boiling range, °C:</b>	Initial boiling point (oil base) > 300
<b>Melting Point, °C:</b>	< -24
<b>Flash Point, °C:</b>	> 160 (ASTM D92, COC)
<b>Autoflammability/ ignition, °C:</b>	> 300 (oil base)
<b>Upper explosion limit:</b>	Not known
<b>Lower explosion limit:</b>	Not known
<b>Vapour pressure, 20 °C, kPa:</b>	< 0.01 (oil base)
<b>Viscosity, kinematic, 40 °C, mm<sup>2</sup>/s:</b>	Indicated by grade designation.
<b>Relative density, 15 °C:</b>	0.85 - 0.89
<b>Water solubility:</b>	Not soluble
<b>Partition coefficient, n-octanol/water:</b>	Not known
<b>Other data:</b>	

## 10. STABILITY AND REACTIVITY

<b>Conditions / materials to avoid:</b>	Stable. May react with strong oxidizing agents.
<b>Hazardous decomposition products:</b>	Thermal decomposition or incomplete combustion may produce oxides of carbon and irritating fumes.

## 11. TOXICOLOGICAL INFORMATION

<b>Eyes:</b>	Unlikely to cause eye irritation.
<b>Skin:</b>	Although incidental contact with the skin does not cause immediate irritation, prolonged and repeated contact may defat the skin and eventually cause dermatitis.
<b>Inhalation:</b>	Not volatile. It is not likely to be an inhalation hazard at normal ambient temperatures. If overheated, fumes and vapours are irritating to the breathing passages and lungs.
<b>Ingestion:</b>	Ingestion is unlikely to cause adverse systemic health effects.
<b>Other:</b>	The refined mineral base oils used in the formulation of this product are of a low order of toxicity in test animals. LD50 (rat) for base oils is above 5 g/kg.

## 12. ECOLOGICAL INFORMATION

<b>Mobility:</b>	Little mobility in soil. Some components may penetrate the soil causing ground water pollution. Will spread on the water surface. A small portion may be dispersed in water.
<b>Degradability:</b>	Not readily biodegradable.
<b>Ecotoxicity/bioaccumulation:</b>	The base oil components are not expected to be dangerous to the aquatic environment. Contains a small amount of additive components classified as dangerous to the aquatic environment. WGK:1

## 13. DISPOSAL CONSIDERATIONS

Transport to authorized waste location, or incinerate under controlled conditions (EU Directives 2000/76/EC and 1999/31/EC apply).  
European Waste Catalogue Code. 130110: mineral based non-chlorinated hydraulic oils

## 14. TRANSPORT INFORMATION

<b>UN-no:</b>	Not classified
<b>RID / ADR:</b>	Not classified
<b>IMO:</b>	Not classified
<b>IATA / ICAO:</b>	Not classified
<b>Other:</b>	

## 15. REGULATORY INFORMATION

<b>EC Labelling / Classification:</b>	
<b>Symbol(s):</b>	None
<b>Contains:</b>	
<b>R phrases:</b>	None
<b>S phrases:</b>	None
<b>Other regulations:</b>	

## 16. OTHER INFORMATION

Text of R-phrases indicated for the ingredients in section 2:  
R 51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.